

CORDLESS DRIVER DRILLS

Cordless

Chargers/
Batteries

Drilling

Demolition

DB 3DL2

3.6V Cordless Driver Drill

Li-ion



Can be converted from L shape to straight shape.

Features

- Convertible to use in angled or straight
- Spindle lock mechanism
- Adjustable clutch: 21-stage torque
- Equipped with battery protection circuit
- With LED light



| Specifications | | |
|-----------------------|---|------------|
| Drive | 6.35mm Hex Bit Shank | |
| Capacity | Mid Steel | 5mm |
| | Wood Screw (D x L) | 3.8 x 38mm |
| | Machine Screw | 5mm |
| Battery Voltage | 3.6V | |
| No Load Speed | High | 600/min |
| | Low | 200/min |
| Torque Setting | 0.3 - 2.9Nm | |
| Overall Length | Straight | 268mm |
| | Angled | 210mm |
| Weight | 0.45kg | |
| Standard Accessories* | 2 Batteries (EBM315), Charger (UC3SFL), Driver Bit, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 8,760/-

Fastening

DB 10DL

10.8V Cordless Driver Drill

Li-ion



Features

- Adjustable clutch: 21-stage torque
- Soft grip handle
- Compact & light weight



| Specifications | | |
|---------------------------|--|------------|
| Drive | 6.35mm Hex Bit Shank | |
| Capacity | Soft wood | 18mm |
| | Wood Screw (D x L) | 6mm x 38mm |
| | Machine Screw | 6mm |
| Battery Voltage | 10.8V | |
| No Load Speed | 0-400/min | |
| Maximum Torque in lock | 10Nm | |
| Torque Setting and Clutch | 1.0-6.0Nm | |
| Overall Length | 147mm | |
| Weight | 0.8kg | |
| Standard Accessories* | Battery (BCL1015 / BCL1030C), Charger (UC10SL2), Driver Bit, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 15,660/-

Grinding

Polishing &
Sanding

Sawing

Cutting

DS 12DA

10.8-12V Peak Cordless Driver Drill

12V PEAK
Li-ion



Features

- 20-stage Clutch
- LED light
- Compact & light weight
- Keyless chuck



| Specifications | | |
|-----------------------|--|-------------|
| Drill Chuck | 0.8-10mm Keyless | |
| Capacity | Mild Steel | 10mm |
| | Soft Wood | 29mm |
| | Wood Screw | 5.8mm |
| | Machine Screw | 6mm |
| Battery Voltage | 10.8-12V Peak | |
| No Load Speed | High | 0-1,400/min |
| | Low | 0-350/min |
| Max Torque Hard | 38Nm | |
| Max Torque Soft | 15Nm | |
| Torque Setting | 0.6 -4.0Nm | |
| Overall Length | 166mm | |
| Weight | 1.1kg with BSL1225M/BSL1215 | |
| | 1.2kg with BSL1240M | |
| Standard Accessories* | 2 Batteries (BSL1225M), Charger (UC12SL), Battery Cover, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 20,000/-

Planing &
Routing

Miscellaneous

Pneumatic



DS 18DA
18V Cordless Driver Drill

Li-ion

Features

- Compact and lightweight
- High capacity battery with battery level indicator
- 20 Stage clutch
- 2 Speed gear

| Specifications | | |
|-----------------------|---|---------------------------------------|
| Drill Chuck | 2.0-13mm Keyless | |
| Capacity | Mild Steel | 13mm |
| | Soft Wood | 36mm |
| | Wood Screw (D X L) | 6 x 75mm |
| | Machine Screw | 6mm |
| Battery Voltage | 18V | |
| No Load Speed | High | 0-1,400/min |
| | Low | 0-350/min |
| Max Torque Hard | 50Nm | |
| Max Torque Soft | 18Nm | |
| Overall Length | 173mm | |
| Weight | Kg | 1.3kg (BSL1820M), 1.9kg (BSL36B18) |
| Standard Accessories* | 2 Batteries (BSL1820M), Charger (UC18YKSL / UC18YSL3), Driver Bit, Battery Cover, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 17,500/-



DS 18DE
18V Cordless
Driver Drill



RFC*
REACTIVE FORCE CONTROL
BRUSHLESS

Features

- 155 mm compact head
- Easy to Use in Tight Spaces
- Drills Fast and Easy
- Reactive Force Control

| Specifications | | |
|-----------------------|--|------------|
| Drill Chuck | 1.5 - 13mm Keyless | |
| Capacity | Brick | 13mm |
| | Mild Steel | 13mm |
| | Soft Wood | 52mm |
| | Wood Screw (DxL) | 10x100mm |
| | Machine Screw | 6mm |
| Battery Voltage | 18V | |
| No Load Speed | High | 0-2000/min |
| | Low | 0-550/min |
| Max Torque | High | 70Nm |
| | Soft | 40Nm |
| Overall Length | 155mm | |
| Weight | 1.7kg (with BSL1840M) 1.9kg (with BSL1850MA / BSL36A18) 2.2kg (with BSL36B18) | |
| Standard Accessories* | 2 Batteries (BSL1840M / BSL1850MA / BSL36A18), Charger (UC18YFSL / UC18YSL3), Driver Bit, Hook, Battery Cover, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 14,620/-
(Bare Tool)-



Brake



Variable Speed



Reversible



2-speed Gear

- Cordless
- Chargers/ Batteries
- Drilling
- Demolition
- Fastening
- Grinding
- Polishing & Sanding
- Sawing
- Cutting
- Planing & Routing
- Miscellaneous
- Pneumatic

DV 18DC

18V Cordless Impact Driver Drill

Li-ion
BRUSHLESS
RFC
REACTIVE FORCE CONTROL

Features

- 190 mm compact head
- Side handle is easy to use and easily adjustable at 11 different positions

Specifications

| | | |
|-----------------------|---|-------------|
| Drill Chuck | 1.5 - 13mm Keyless | |
| Capacity | Brick | 20mm |
| | Mild Steel | 16mm |
| | Soft Wood | 102mm |
| | Wood Screw (DxL) | 12x100 mm |
| | Machine Screw | 6mm |
| Battery Voltage | 18V | |
| No Load Speed | High | 0-2,000/min |
| | Low | 0-500/min |
| Impact Rate | 0-30,000/min | |
| Max Torque | Hard | 140Nm |
| | Soft | 70Nm |
| Overall Length | 190mm | |
| Weight | 2.6kg (with BSL1840M) | |
| | 2.8kg (with BSL36A18 / BSL1850MA) | |
| | 3.1kg (with BSL36B18) | |
| Standard Accessories* | 2 Batteries (BSL36A18 / BSL1850MA / BSL1840M), Charger (UC18YSL3 / UC18YFSL), Driver Bit, Side Handle, Hook, Battery Cover, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 45,946/-



WH 7DL

7.2V Cordless Impact Driver

Can be converted from L shape to straight shape.



Li-ion

Features

- Convertible to use in angled or straight
- Automatic spindle lock mechanism for manual tightening



Specifications

| | | |
|-----------------------|---|-------|
| Capacity | Bolt | 3-8mm |
| | High Tension Bolt | 3-6mm |
| | Small Screw | 3-8mm |
| Drive | 6.35mm Hex Bit Shank | |
| Tightening Torque | 25Nm | |
| Battery Voltage | 7.2V | |
| No Load Speed | 0-2,400/min | |
| Full Load Impact Rate | 0-3,000/min | |
| Overall Length | Straight | 282mm |
| | L shape | 211mm |
| Weight | 0.59kg | |
| Standard Accessories* | Batteries (BCL715), Charger (UC7SL), Battery Cover, Carrying Case | |

MRP: ₹ 16,140/-

*Standard accessories may vary by country or area

CR 18DBL

Cordless
Reciprocating Saw

Li-ion
BRUSHLESS
LVH
LOW VIBRATION HANDLE

Features

- Brushless motor control allows max speed (SPM) adjustment With auto mode, electricity consumption and noise can be suppressed by lowering the number of maximum strokes during no-load motor operation
- Tool-less blade change
- Tool-less shoe adjustment
- Easy to grip and handle
- Large pivoting hook conveniently allows for hanging the tool on a ϕ 48mm pipe



| Specifications | | |
|-----------------------|--|-------|
| Battery Voltage | 18V | |
| Capacity | Mild Steel Pipe | 130mm |
| | PVC Pipe | 130mm |
| | Wood | 120mm |
| | Mild Steel Plate | 19mm |
| No Load Speed | 0 - 2,500/min | |
| Length of Stroke | 32mm | |
| Overall Length | 435mm | |
| Weight | 3.4kg* | |
| Standard Accessories* | 2 Batteries BSL36A18 or BSL1850MA, Charger (UC18YSL3), Blade for Wood, Hex. Bar Wrench, Battery Cover, Carrying Case | |



MRP: ₹ 52,581/-

*Standard accessories may vary by country or area

CB 18DBL

Cordless Band Saw

Li-ion
BRUSHLESS

Features

- Auto Mode function
- Soft start function
- High speed cutting with a cleaner finish



| Specifications | | |
|-----------------------|--|-------------------|
| Battery Voltage | 18V | |
| Capacity | Round pipe (external diameter) | 83mm |
| | Square pipe (WxH) | 80x80mm |
| Cutting Speed | Standard mode | 80 - 195 (m/min) |
| | Auto mode (without load) | 120 - 195 (m/min) |
| Dimensions | Length | 413mm |
| | Width | 173mm |
| | Height | 266mm |
| Blade size | 900 x 12.5 x 0.5mm | |
| Length of Stroke | 32mm | |
| Overall Length | 435mm | |
| Weight | 3.6kg (with BSL36A18 battery) | |
| Standard accessories* | 2 Batteries BSL36A18 or BSL1850MA, Charger (UC18YSL3), 1 x 18TPI bi-metal blade, side handle and wrench. 3.6kg (with BSL36A18 battery) | |

MRP: ₹ 52,734/-

*Standard accessories may vary by country or area



Brake



Variable Speed



Electronic Constant Speed Control

CORDLESS DRIVER DRILLS

DS 36DC
MULTI VOLT 36V
Cordless Driver Drill

Li-ion
BRUSHLESS
RFC
REACTIVE FORCE CONTROL

Features

- Powerful enough to drill 36mm holes easily
- Continuously drives thick and long screws fast
- 190mm compact head
- Side handle is easy to use and easily adjustable at 11 different positions

| Specifications | | |
|-----------------------|---|-------------|
| Drill Chuck | 1.5-13mm Keyless | |
| Capacity | Mild Steel | 20mm |
| | Soft Wood | 118mm |
| | Wood Screw | 16x100mm |
| | Machine Screw | 6mm |
| Battery Voltage | 36V | |
| No Load Speed | High | 0-2,200/min |
| | Low | 0-550/min |
| Max Torque Hard | 155Nm | |
| Max Torque Soft | 100Nm | |
| Overall Length | 190mm | |
| Weight | 2.8kg (with BSL36A18) | |
| | 3.1kg (with BSL36B18) | |
| Standard Accessories* | 2 Batteries (BSL36A18), Charger (UC18YSL3), Side Handle, Hook, Driver Bit, Battery Cover, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 48,000/-



Higher Drilling Capacity
and Greater Versatility with
MULTI VOLT Battery



CORDLESS IMPACT DRIVER DRILLS

DV 36DA
MULTI VOLT 36V Cordless Impact Driver Drill

Li-ion
BRUSHLESS
RFC
REACTIVE FORCE CONTROL



Higher Drilling Capacity and Greater Versatility with MULTI VOLT Battery



Features

- Feedback speed control for more stable handling
- Robust aluminium gear case
- 22-stage adjustable clutch
- Large double-molded clutch dial is easy to grip and read

Specifications

| | | |
|-----------------------|---|--------------|
| Drill Chuck | 1.5–13mm Keyless | |
| Capacity | Brick | 20mm |
| | Mild Steel | 16mm |
| | Soft Wood | 102mm |
| | Wood Screw | 12x100mm |
| | Machine Screw | 6mm |
| Battery Voltage | 36V | |
| No Load Speed | High | 0–2,100/min |
| | Low | 0–500/min |
| Impact Rate | High | 0–31,500/min |
| | Low | 0–7,500/min |
| Max Torque Hard | 138Nm | |
| Max Torque Soft | 64Nm | |
| Torque Setting | 2–8Nm | |
| Overall Length | 204mm | |
| Weight | 2.7kg-3.0kg | |
| Standard Accessories* | 2 Batteries (BSL36A18), Charger (UC18YSL3), Side Handle, Driver Bit, Battery Cover, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 60,000/-



Brake



Variable Speed



Reversible



2-speed Gear

Cordless
Chargers/
Batteries
Drilling
Demolition
Fastening
Grinding
Polishing &
Sanding
Sawing
Cutting
Planing &
Routing
Miscellaneous
Pneumatic

CORDLESS IMPACT DRIVER

WH 36DB
MULTI VOLT 36V
Cordless Impact Driver

IP56

**TRIPLE
HAMMER**



MULTI VOLT
High-Speed Fastening
throughout the Battery
Charge

Li-ion BRUSHLESS

Features

- Triple Hammer mechanism has three strikers making three impacts per rotation instead of the usual two, reducing vibration and vastly improving user comfort
- 4-step tightening mode selector for a variety of jobs from delicate to heavy duty work
- Newly designed airflow system for optimal cooling efficiency
- Well-balanced weight distribution for better work efficiency
- IP56 dust & water resistance



Specifications

| | | |
|-----------------------|---|-------------|
| Capacity | Bolt | 5-18mm |
| | High Tension Bolt | 5-14mm |
| | Machine Screw | 4-10mm |
| | Self Drilling Screw | 3.5-6mm |
| Drive | 6.35mm Hex Bit Shank | |
| Tightening Torque | 210Nm | |
| Battery Voltage | 36V | |
| No Load Speed | Power Mode | 0-2,900/min |
| | Normal Mode | 0-2,900/min |
| | Soft Mode | 0-900/min |
| | Self Drilling Screw Mode | 0-2,900/min |
| Impact Rate | Power Mode | 0-4,100/min |
| | Normal Mode | 0-4,100/min |
| | Soft Mode | 0-2,000/min |
| | Self Drilling Screw Mode | 0-2,200/min |
| Overall Length | 127mm | |
| Weight | 1.6kg-1.9kg | |
| Standard Accessories* | 2Batteries (BSL36A18), Charger (UC18YSL3), Battery Cover, Carrying Case | |



*Standard accessories may vary by country or area

MRP: ₹ 52,500/-



CORDLESS IMPACT DRIVER



WH 36DC
MULTI VOLT 36V
Cordless Impact Driver

IP56
TRIPLE HAMMER

Li-ion BRUSHLESS

Features

- Compact head and lightweight design
- 5 tightening modes for various applications
- Triple LED lights for superior visibility
- IP56 dust & water resistance

| Specifications | | |
|------------------------|--|-------------|
| Capacity | Small Screw | 4 - 10mm |
| | Ordinary Bolt | 5-18mm |
| | High Tension Bolt | 5-14mm |
| | Self Drilling Screw | ø3.5-ø6mm |
| Drive | 6.35mm Hex Bit Shank | |
| Max. Tightening Torque | 215Nm | |
| Battery Voltage | 36V | |
| No Load Speed | Soft Mode | 0-900/min |
| | Power Mode | 0-3,400/min |
| | Bolt Mode | 0-2,900/min |
| | Bolt Single Mode | 0-2,900/min |
| | Self Drilling Screw Mode | 0-3,700/min |
| Impact Rate | Soft Mode | 0-2,000/min |
| | Power Mode | 0-4,100/min |
| | Bolt Mode | 0-4,100/min |
| | Bolt Single Mode | 0-4,100/min |
| | Self Drilling Screw Mode | 0-2,200/min |
| Overall Length | 114mm | |
| Weight | 1.6kg | |
| Standard Accessories* | 2 Batteries (BSL36A18), Charger (UC18YSL3), Battery Cover, Carrying Case | |

*Standard accessories may vary by country or area



MRP: ₹ 17,340/-
(Bare Tool)

- Cordless
- Chargers/ Batteries
- Drilling
- Demolition
- Fastening
- Grinding
- Polishing & Sanding
- Sawing
- Cutting
- Planing & Routing
- Miscellaneous
- Pneumatic

CORDLESS IMPACT WRENCH



MULTI VOLT

IP56

WR 36DF
MULTI VOLT 36V
Cordless Impact Wrench



Li-ion
BRUSHLESS



Features

- 1,900Nm Tightening Torque
- 2,400Nm Nut Busting Torque
- Variable Speed Control
- 4-Stage Tightening mode selector
- IP56 Dust and Water Resistant*
- Powered by 36V High Performance brushless motor
- Bright LED light

Specifications

| | | |
|-----------------------|---|-------------|
| Capacity | Bolt | M12-M36 |
| | High Tension Bolt | M10-M27 |
| Square Drive | 19mm | |
| Tightening Torque | 1,900Nm | |
| Nut Busting Torque | 2,400Nm | |
| Battery Voltage | 36V | |
| No Load Speed | Mode 4 | 0-1,500/min |
| | Mode 3 | 0-1,200/min |
| | Mode 2 | 0-900/min |
| | Mode 1 | 0-600/min |
| Full Impact Rate | Mode 4 | 0-2,600/min |
| | Mode 3 | 0-2,200/min |
| | Mode 2 | 0-1,900/min |
| | Mode 1 | 0-1,600/min |
| Overall Length | 221mm | |
| Weight | 3.9kg (BSL36A18) | |
| Standard Accessories* | Charger (UC 18YSL3), Battery (BSL36A18) - 2 Nos, stackable case, battery cover. | |



*Standard accessories may vary by country or area
* Above image is for illustration purpose only.

MRP: ₹ 52,000/-



CORDLESS IMPACT WRENCH



IP56

WR 36DG
MULTI VOLT 36V
Cordless Impact Wrench



Li-ion
BRUSHLESS



Features

- 1,400Nm Tightening Torque
- 2,000Nm Nut Busting Torque
- Variable Speed Control
- 4-Stage Tightening mode selector
- IP56 Dust and Water Resistant*
- Powered by 36V High Performance brushless motor
- Bright LED light

| Specifications | | |
|-----------------------|---|-------------|
| Capacity | Bolt | M12–M33 |
| | High Tension Bolt | M10–M24 |
| Square Drive | 12.7mm | |
| Tightening Torque | 1,400Nm | |
| Nut Busting Torque | 2,000Nm | |
| Battery Voltage | 36V | |
| No Load Speed | Mode 4 | 0–1,500/min |
| | Mode 3 | 0–1,200/min |
| | Mode 2 | 0-900/min |
| | Mode 1 | 0–600/min |
| Full Impact Rate | Mode 4 | 0–2,500/min |
| | Mode 3 | 0–2,200/min |
| | Mode 2 | 0–1,900/min |
| | Mode 1 | 0–1,600/min |
| Overall Length | 221mm | |
| Weight | 3.9kg (BSL36A18) | |
| Standard Accessories* | Charger (UC 18YSL3), Battery (BSL36A18) - 2 Nos, stackable case, battery cover. | |



*Standard accessories may vary by country or area
* Above image is for illustration purpose only.

MRP: ₹ 53,000/-

- Cordless
- Chargers/ Batteries
- Drilling
- Demolition
- Fastening
- Grinding
- Polishing & Sanding
- Sawing
- Cutting
- Planing & Routing
- Miscellaneous
- Pneumatic



Variable Speed



Reversible



Brake

CORDLESS DISC GRINDER



G 3610DA
 MULTI VOLT 36V
 Cordless Disc Grinder
 with Slide Switch



Li-ion
BRUSHLESS

Features

- Faster grinding & cutting speed
- 146mm grip circumference
- Auto Mode adjusts the speed automatically between high and low speeds depending on the load
- Electronic brake stops the wheel in less than 2 seconds
- Kickback protection system
- Anti-restart protection
- Variable speed control

Specifications

| | | |
|-----------------------|---|-----------------|
| Capacity | Wheel Dia. | 100mm |
| | Hole Dia. | 16mm |
| Spindle Thread | M10x1.5 | |
| Voltage | 36V | |
| No Load Speed | Transmission Mode | 3,000-9,500/min |
| | Auto Mode | 5,500/min |
| Overall Length | 358mm | |
| Weight | 2.6kg | |
| Standard Accessories* | 2 Batteries (BSL36A18), Charger (UC18YSL3), Depressed Center Wheel (100mm dia.), Side Handle, Wrench, 2 Battery Covers, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 48,000/-



CORDLESS DISC GRINDER

G 3610DVE
MULTI VOLT 36V
Cordless Disc Grinder

Li-ion
BRUSHLESS



Higher Drilling Capacity
and Greater Versatility with
MULTI VOLT Battery

Features

- 1,500W max output
- Highly durable ball bearings
- Dust and water resistant switch
- After the motor has stopped due to overloading, it continues to run if the load decreases within 1.5 seconds
- Small grip circumference
- Variable speed control with auto mode
- Dual LEDs illuminate both sides of the wheel
- 3 position side handle
- Easy to maintain mesh dust filter
- Kickback protection
- Drop shut-off function
- Restart protection



Specifications

| | | |
|-----------------------|---|--------------------|
| Battery Voltage | 36V | |
| Capacity | Wheel Dia. | 100mm |
| | Hole Dia. | 16mm |
| | Thickness. | 6mm |
| No Load Speed | AUTO Mode | 5,500/min |
| | Transmission Mode | 3,200 - 10,000/min |
| Spindle Thread | M10 x 1.5 | |
| Overall Length | 375mm* | |
| Weight | 2.8kg (with BSL36A18) | |
| | 3.0kg (with BSL36B18) | |
| Standard accessories* | 2 Batteries (BSL36A18), Charger (UC18YSL3), Side Handle, Wheel Guard, Depressed Center Wheel, Wrench, 2 Battery Covers, Carrying Case | |

*Standard accessories may vary by country or area



MRP: ₹ 48,000/-



Electronic Soft Start Control



Variable Speed



Spindle Lock



Brake

- Cordless
- Chargers/Batteries
- Drilling
- Demolition
- Fastening
- Grinding
- Polishing & Sanding
- Sawing
- Cutting
- Planing & Routing
- Miscellaneous
- Pneumatic



CORDLESS DISC GRINDER

G 3618DA
 MULTI VOLT 36V
 Cordless Disc Grinder
 with Slide Switch

Li-ion
BRUSHLESS



Features

- High performance with brushless motor
- Trigger switch with ON/OFF lock
- Brake, kickback, anti-restart & soft start function
- Soft grip & anti-vibration side handle
- Tool-less wheel guard

Specifications

| | | |
|----------------|---|-----------|
| Capacity | Wheel Dia. | 180mm |
| | Hole Dia. | 22.23mm |
| Spindle Thread | M14x2 | |
| Voltage | 36V | |
| No Load Speed | Normal Mode | 5,300/min |
| | Auto Mode | 3,200/min |
| Overall Length | 531mm | |
| Weight | 4.7kg (Without Battery) | |
| Accessories | 2 Batteries (BSL36A18), Charger (UC18YSL3), Depressed Center Wheel (180mm dia.), Side Handle, Wrench, 2 Battery Covers, Carrying Case | |

*Standard accessories may vary by country or area



MRP: ₹ 35,600/-
(Bare Tool)

Cordless

Chargers/
Batteries

Drilling

Demolition

Fastening

Grinding

Polishing &
Sanding

Sawing

Cutting

Planing &
Routing

Miscellaneous

Pneumatic



CORDLESS RECIPROCATING SAW

CR 36DA
MULTI VOLT 36V
Reciprocating Saw

**Li-ion
BRUSHLESS**

UVP
US-VIBRATION PROTECTION



Features

- Orbital Mode for maximum wood cutting approx. 194% faster cutting speed
- HiKOKI Twin-counterweight System for significant vibration reduction
- Four-mode speed control for a variety of applications
- Tool-less blade change
- Tool-less shoe adjustment
- Durable cylindrical housing
- Large pivoting hook

| Specifications | | |
|-----------------------|---|-------|
| Battery Voltage | 36V | |
| Capacity | Mild Steel Pipe | 130mm |
| | Vinyl Chloride Pipe. | 130mm |
| | Wood | 300mm |
| | Mild Steel Plate | 19mm |
| No Load Speed | 0 - 3,000/min | |
| Length of Stroke | 32mm | |
| Overall Length | 457mm | |
| Weight | 4.5kg with BSL36A18 battery | |
| Standard accessories* | 2 Batteries BSL36A18, Charger (UC18YSL3), Blade, Battery Cover, Carrying Case | |

*Standard accessories may vary by country or area

MRP: ₹ 72,017/-



Brake



Variable Speed



2-speed Gear



Orbital Cutting Action

- Cordless
- Chargers/ Batteries
- Drilling
- Demolition
- Fastening
- Grinding
- Polishing & Sanding
- Sawing
- Cutting
- Planing & Routing
- Miscellaneous
- Pneumatic

10 mm TOOL KIT



| Specifications | | |
|---------------------------|----------------|------|
| Drill Chuck | 1.5-10mm | |
| Capacity | Metal | 10mm |
| | Masonry | 10mm |
| | Wood | 20mm |
| Power Input | 550W | |
| No Load Speed | 0-3,000/min | |
| Dimension(L*W*H) | (290x66x100)mm | |
| Full Load Impact Rate | 0-48,000/min | |
| Package | BMC | |
| Weight | 1.7kg | |
| 28 Pieces Accessories kit | | |

MRP: ₹ 6,240/-

13 mm TOOL KIT



| Specifications | | |
|---------------------------|-----------------|------|
| Drill Chuck | 1.5-13mm | |
| Capacity | Concrete | 13mm |
| | Steel | 13mm |
| | Wood | 20mm |
| Power Input | 550W | |
| No Load Speed | 0-2,900/min | |
| Dimension(L*W*H) | (325x260x790)mm | |
| Full Load Impact Rate | 29,000/min | |
| Overall Length | 270mm | |
| Package | BMC | |
| Weight | 1.7kg | |
| 28 Pieces Accessories kit | | |

MRP: ₹ 6,800/-

D 10VSTA
10mm Drill

375702



Features

- Soft grip handle
- Variable & reversible mode

| Specifications | | |
|----------------------|--------------|------|
| Chuck Capacity | 1.5-10mm | |
| Capacity | Steel | 10mm |
| | Wood | 20mm |
| Power Input | 450W | |
| No Load Speed | 0-3,000/min | |
| Overall Length | 245mm | |
| Weight | 1.3kg | |
| Standard Accessories | Chuck Wrench | |

MRP: ₹ 3,060/-

D 13VH
13mm Drill

999041



Features

- Chuck offset 23.5mm
- Aluminium Gear Cover for durability
- Soft grip handle
- Variable speed by trigger and dial

| Specifications | | |
|----------------------|--|------|
| Chuck Capacity | 1.5-13mm Keyed / keyless | |
| Capacity | Steel | 13mm |
| | Wood | 40mm |
| Power Input | 690W | |
| No Load Speed | Hi: 0-3,000/min Lo: 0-1,000/min | |
| Overall Length | 333mm | |
| Weight | 1.9kg | |
| Standard Accessories | Chuck Wrench, Side Handle, Depth Stopper | |

MRP: ₹ 8,840/-



Double Insulation



Variable Speed



Reversible



2-speed Gear

IMPACT DRILLS

Cordless

Chargers/
Batteries

Drilling

DV 10VST 10mm Impact Drill

374185 

Features

- Soft grip for easier handling
- Variable speed trigger to suit multiple drilling application
- Forward & reversible for convenience



| Specifications | | |
|-----------------------|---|------|
| Drill Chuck | 1.5-10mm | |
| Capacity | Metal | 10mm |
| | Masonry | 10mm |
| | Wood | 20mm |
| Power Input | 550W | |
| No Load Speed | 0-3,000/min | |
| Full Load Impact Rate | 0-48,000/min | |
| Overall Length | 290mm | |
| Weight | 1.7kg | |
| Standard Accessories | Side Handle, Depth Stopper, Accessory Kit | |


MRP: ₹ 3,630/-

Demolition

Fastening

Grinding

DV 13VSS 13mm Impact Drill

999041 

Features

- Cylindrical housing for durability
- Offset of chuck: 28mm
- Variable speed by dial & trigger



| Specifications | | |
|-----------------------|-------------|------|
| Drill Chuck | 1.5-13mm | |
| Capacity | Concrete | 13mm |
| | Steel | 13mm |
| | Wood | 20mm |
| Power Input | 550W | |
| No Load Speed | 0-2,900/min | |
| Full Load Impact Rate | 29,000/min | |
| Overall Length | 270mm | |
| Weight | 1.4kg | |

MRP: ₹ 4,950/-

Polishing &
Sanding

Sawing

Cutting

DV 16V 16mm Impact Drill

999041 

Features

- Cylindrical Housing for durability



| Specifications | | |
|-----------------------|---|------|
| Drill Chuck | 1.5-13mm | |
| Capacity | Concrete | 16mm |
| | Steel | 13mm |
| Power Input | 590W | |
| No Load Speed | 0-2,900/min | |
| Full Load Impact Rate | 34,500/min | |
| Overall Length | 269mm | |
| Weight | 1.5kg | |
| Standard Accessories | Side Handle, Depth Gauge, Carrying Case, Chuck Wrench | |


MRP: ₹ 7,720/-

Planing &
Routing

Miscellaneous

Pneumatic

VTP 18 18mm Impact Drill

999041 

Features

- Metal gear housing
- With 2 speed



| Specifications | | |
|-----------------------|-------------------|-----------|
| Voltage | 220V | |
| Drill Chuck | 1.5 - 13mm | |
| Speed change | 1 | 2 |
| No-load speed | 1,050/min | 1,800/min |
| Capacity Steel | 13mm | 8mm |
| Capacity Concrete | 18mm | 10mm |
| Power Input | 640W | |
| Full Load Impact Rate | 17,800-28,600/min | |
| Overall Length | 340mm | |
| Weight | 2.3Kg | |

MRP: ₹ 8,950/-



HIKOKI



ROTARY HAMMERS

Experttoolings

ROTARY HAMMERS

DH 22PBS


22mm Rotary Hammer

374908



Features

- 2-mode action: Rotation & Hammering mode and Rotation only mode
- SDS Plus shank
- Variable speed trigger
- Drilling / Hammer Drilling



| Specifications | | |
|-----------------------|------------|------|
| Capacity | Concrete | 22mm |
| | Mild Steel | 13mm |
| | Wood | 25mm |
| Power Input | 820W | |
| No load RPM | 0-1100/min | |
| Full Load Impact rate | 4400/min | |
| Overall Length | 385mm | |
| Weight | 2.8kg | |

MRP: ₹ 14,000/-

DH 24PG2


24mm Rotary Hammer

999041



Features

- 2-mode action: Rotation and Hammering mode and Rotation only mode
- Compact design
- Labyrinth Ventilation windows



| Specifications | | |
|-----------------------|---|------|
| Capacity | Concrete | 24mm |
| | Mild Steel | 13mm |
| | Wood | 32mm |
| | Core Bit | 50mm |
| Power Input | 730W | |
| Bit Shank | SDS-plus | |
| No Load Speed | 0-1,050/min | |
| Full Load Impact rate | 0-3,950/min | |
| Overall Length | 349mm | |
| Weight | 2.8kg | |
| Standard Accessories | Side Handle, Depth Gauge, Carrying Case | |

MRP: ₹ 15,450/-

DH 26PB2


26mm Rotary Hammer

999041



Features

- 2-mode action: Rotation and Hammering mode and Rotation only mode
- Highest drilling speed
- Labyrinth ventilation windows



| Specifications | | |
|-----------------------|---|------|
| Capacity | Concrete | 26mm |
| | Mild Steel | 13mm |
| | Wood | 32mm |
| | Core Bit | 50mm |
| Power Input | 830W | |
| Bit Shank | SDS-plus | |
| No Load Speed | 0-1,100/min | |
| Full Load Impact rate | 0-4,300/min | |
| Overall Length | 349mm | |
| Weight | 2.8kg | |
| Standard Accessories | Side Handle, Depth Gauge, Carrying Case | |

MRP: ₹ 16,160/-




DH 26PC2
26mm Rotary Hammer



Features

- 3-mode action: Rotation and Hammering mode, Rotation only mode and Hammering mode only.
- Labyrinth ventilation windows
- Compact body



- Double Insulation
- 🔄 Variable Speed
- 👁️ Reversible
- fs+ SLOW Clutch
- SDS plus Shank
- 🔧 Slip Clutch
- ⬆️ Rotation only
- ⬆️ Rotation & Hammering

| Specifications | | |
|-----------------------|---|---------|
| Capacity | Concrete | 26mm |
| | Mild Steel | 13mm |
| | Wood | 32mm |
| | Core bit | 25-50mm |
| Power Input | 830W | |
| Bit Shank | SDS-plus | |
| No-Load Speed | 0-1,100min | |
| Full Load Impact rate | 0-4,300min | |
| Overall Length | 349mm | |
| Weight | 2.8kg | |
| Standard Accessories | Side Handle, Depth Gauge, Carrying Case | |


MRP: ₹ 17,950/-

DH 28PB2
28mm Rotary Hammer



Features

- 2-mode action: Rotation and Hammering mode and Rotation only mode.
- Lowest vibration in its class through UVP system using dynamic damper
- Labyrinth ventilation windows
- Large mode change lever



- Double Insulation
- 🔄 Variable Speed
- 👁️ Reversible
- fs+ SLOW Clutch
- SDS plus Shank
- 🔧 Slip Clutch
- ⬆️ Rotation only
- ⬆️ Rotation & Hammering

| Specifications | | |
|-----------------------|---|------|
| Capacity | Concrete | 28mm |
| | Mild Steel | 13mm |
| | Wood | 32mm |
| | Core Bit | 50mm |
| Power Input | 850W | |
| Bit Shank | SDS-plus | |
| No Load Speed | 0-1,100/min | |
| Full Load Impact rate | 0-4,300/min | |
| Overall Length | 360mm | |
| Weight | 3.0kg | |
| Standard Accessories | Side Handle, Depth Gauge, Carrying Case | |

MRP: ₹ 17,280/-

DH 28PC2
28mm Rotary Hammer



Features

- 3-mode action: Rotation and Hammering mode, Rotation only mode and Hammering mode only.
- Lowest vibration in its class through UVP system using dynamic damper
- One push bit mounting



- Double Insulation
- 🔄 Variable Speed
- 👁️ Reversible
- fs+ SLOW Clutch
- SDS plus Shank
- 🔧 Slip Clutch
- ⬆️ Rotation only
- ⬆️ Rotation & Hammering

| Specifications | | |
|-----------------------|---|------|
| Capacity | Concrete | 28mm |
| | Mild Steel | 13mm |
| | Wood | 32mm |
| | Core Bit | 50mm |
| Power Input | 850W | |
| Bit Shank | SDS-plus | |
| No Load Speed | 0-1,100/min | |
| Full Load Impact rate | 0-4,300/min | |
| Overall Length | 360mm | |
| Weight | 3.0kg | |
| Standard Accessories | Side Handle, Depth Gauge, Carrying Case | |

MRP: ₹ 20,080/-

ROTARY HAMMERS

Cordless

Chargers/
Batteries

Drilling

Demolition

DH 40MC 40mm Rotary Hammer



999043

Features

- Large change lever
- Multiple bit angle setting.

| Specifications | | |
|-----------------------|--|-------|
| Capacity | Drill Bit | 40mm |
| | Core Bit | 105mm |
| Power Input | 1,100W | |
| Bit Shank | SDS max | |
| No Load Speed | 620/min | |
| Full Load Impact rate | 2,800/min | |
| Overall Length | 448mm | |
| Weight | 7.1kg | |
| Standard Accessories | Side Handle, Stopper, Hammer Grease A (30g), Carrying Case | |



MRP: ₹ 43,430/-

Fastening

Grinding

Polishing &
Sanding

Sawing

DH 45MA 45mm Rotary Hammer



999044

Features

- Powerful 1,400W motor delivers the power needed for heavy-duty applications
- Large change lever for easy and smooth mode switching
- Easy to hold large trigger switch

| Specifications | | |
|-----------------------|---|-------|
| Capacity | Drill bit | 45mm |
| | Core bit | 125mm |
| Power Input | 1,400W | |
| Bit Shank | SDS max | |
| No Load Speed | 380/min | |
| Full Load Impact rate | 2,900/min | |
| Overall Length | 535mm | |
| Weight | 9.4kg | |
| Standard Accessories | Side Handle, Stopper, Rotary Hammer Grease A, Carrying Case | |



MRP: ₹ 60,080/-

Cutting

Planing &
Routing

Miscellaneous

Pneumatic

DH 45ME 45mm Rotary Hammer



Features

- Maintains the speed and performance even at voltage drop
- Power lamp lights up when the plug is inserted into an outlet
- Large mode change lever
- Large trigger switch

| Specifications | | |
|-----------------------|---|-------|
| Capacity | Drill bit | 45mm |
| | Core bit | 125mm |
| Power Input | 1,500W | |
| Bit Shank | SDS max | |
| No Load Speed | 220V: 120 - 310/min | |
| Full Load Impact rate | 220V: 1,200 - 2,950/min | |
| Overall Length | 535mm | |
| Weight | 9.0kg | |
| Standard Accessories | Side Handle, Stopper, Rotary Hammer Grease A, Carrying Case | |



MRP: ₹ 72,450/-



DH 52ME
52mm Rotary Hammer

FHB **LVH**
ALUMINUM HOUSING BODY LOW VIBRATION HANDLE
BRUSHLESS



Features

- Maintains the speed and performance even at voltage drop
- Power lamp lights up when the plug is inserted into an outlet
- Large mode change lever
- Large trigger switch



| Specifications | | |
|-----------------------|---|-------|
| Capacity | Drill bit | 52mm |
| | Core bit | 160mm |
| Power Input | 1,500W | |
| Bit Shank | SDS max | |
| No Load Speed | 220V: 110 - 280/min | |
| Full Load Impact rate | 220V: 1,000 - 2,400/min | |
| Overall Length | 585mm | |
| Weight | 11kg | |
| Standard Accessories | Side Handle, Stopper, Rotary Hammer Grease A, Carrying Case | |

MRP: ₹ 94,990/-

Double Insulation
 Electronic Constant Speed Control
 Slip Clutch
 Shock-Absorbing Handle Type
 SDS max Shank
 2-speed Gear



Cordless
Chargers/
Batteries
Drilling
Demolition
Fastening
Grinding
Polishing &
Sanding
Sawing
Cutting
Planing &
Routing
Miscellaneous
Pneumatic

DISC GRINDER

Cordless

G 10SS2

100mm Disc Grinder with Slide Switch



999067

Features

- Newly-designed large fan and optimized air flow ensure efficient motor cooling for a long lifetime
- Small grip circumference of 197mm



Specifications

| | | |
|----------------------|------------------------|-------|
| Capacity | Wheel Dia | 100mm |
| | Hole Dia | 16mm |
| Spindle Thread | M10 x 1.5 | |
| Power Input | 600W | |
| No Load Speed | 11,500/min. : 220-240V | |
| Overall Length | 254mm | |
| Weight | 1.7kg | |
| Standard Accessories | Side Handle, Wrench | |

MRP: ₹ 3,900/-

Chargers/
Batteries

Drilling

Demolition

PDA-100M

100mm Disc Grinder with Snap Switch



999021

Features

- 100mm, 715W mini grinder
- Snap switch easy to use
- Excellent overload durability



Specifications

| | | |
|----------------------|--------------------------------|-------|
| Capacity | Wheel Dia | 100mm |
| | Hole Dia | 16mm |
| Spindle Thread | M10 x 1.5 | |
| Power Input | 715W | |
| No Load Speed | 12,000/min. | |
| Overall Length | 260mm | |
| Weight | 1.5kg | |
| Standard Accessories | Depressed Center Wheel, Wrench | |

MRP: ₹ 5,700/-

Fastening

Grinding

Polishing &
Sanding

G 10SN2

100mm Disc Grinder with Slide Switch



999005

Features

- High power 900W motor provides more efficient work



Specifications

| | | |
|----------------------|---|-------|
| Capacity | Wheel Dia | 100mm |
| | Hole Dia | 16mm |
| Spindle Thread | M10 x 1.5 | |
| Power Input | 900W | |
| No Load Speed | 10,500/min | |
| Overall Length | 266mm | |
| Weight | 1.8kg | |
| Standard Accessories | Side Handle, Depressed Center Wheel, Wrench | |

MRP: ₹ 7,400/-

Sawing

Cutting

Planing &
Routing

Miscellaneous

Pneumatic



G 10VE2
100mm Electronic
Disc Grinder with
Slide Switch



BRUSHLESS

Features

- 3-position side handle
- Kickback protection
- Durable and dust resistant design
- Small grip circumference for more comfort and control
- Variable speed control
- Restart protection
- Soft Start
- After the motor has stopped due to over loading, it gets auto activated if load reduce within 1.5 seconds



| Specifications | | |
|----------------------|----------------------------------|-------|
| Capacity | Wheel Dia | 100mm |
| | Hole Dia | 16mm |
| | Thickness | 6mm |
| Spindle Thread | M10 x 1.5 | |
| Power Input | 1,320W | |
| Max Power Output | 1,900W | |
| No Load Speed | 2,800 - 10,000/min | |
| Overall Length | 309mm | |
| Weight | 1.8kg | |
| Standard Accessories | Wheel Guard, Side Handle, Wrench | |

MRP: ₹ 16,000/-

PDA-125M
125mm Disc Grinder
with Snap Switch



999021

Features

- 125mm, 715W grinder
- Snap switch that is easy to use
- Outer carbon brush for easy maintenance



| Specifications | | |
|----------------------|---------------------|---------|
| Capacity | Wheel Dia | 125mm |
| | Hole Dia | 22.23mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 715W | |
| Overall Length | 260mm | |
| Weight | 2.1kg | |
| Standard Accessories | Side Handle, Wrench | |

MRP: ₹ 7,500/-

G 13SR4
125mm Disc Grinder
with Slide Switch



999067


Features

- Newly-designed large fan and optimized air flow ensure efficient motor cooling for a long lifetime
- Small grip circumference of 197mm



| Specifications | | |
|----------------------|---------------------|---------|
| Capacity | Wheel Dia | 125mm |
| | Hole Dia | 22.23mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 730W | |
| No Load Speed | 10,000/min. | |
| Overall Length | 258mm | |
| Weight | 1.8kg | |
| Standard Accessories | Side Handle, Wrench | |

MRP: ₹ 6,720/-




Cordless
Chargers/
Batteries
Drilling
Demolition
Fastening
Grinding
Polishing &
Sanding
Sawing
Cutting
Planing &
Routing
Miscellaneous
Pneumatic

DISC GRINDER

Cordless

G 13SW

125mm Disc Grinder with Slide Switch

999088 



Features

- Max power output 1,600W
- Tool-less wheel guard
- Vibration-Absorbing side handle
- Small grip circumference (202mm) for more control and comfort



Specifications

| | | |
|----------------------|---|--------|
| Capacity | Wheel Dia | 125mm |
| | Hole Dia | 22.2mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 1,200W | |
| No Load Speed | 12,000/min | |
| Overall Length | 277mm | |
| Weight | 2.3kg | |
| Standard Accessories | Side Handle, Depressed Center Wheel, Wrench | |

MRP: ₹ 8,820/-

Fastening

G 13SB4

125mm Disc Grinder with Slide Switch

999088 



Features

- Toolless wheel guard
- Excellent overload durability
- Improved dust protection against short circuit



Specifications


| | | |
|----------------------|---|--------|
| Capacity | Wheel Dia | 125mm |
| | Hole Dia | 22.2mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 1,400W | |
| No Load Speed | 11,500/min | |
| Overall Length | 288mm | |
| Weight | 2.4kg | |
| Standard Accessories | Side Handle, Depressed Center Wheel, Wrench | |

MRP: ₹ 9,740/-

Cutting

G 15SA2

150mm Disc Grinder with Trigger Switch

999043 



Features

- Max power output 2,100W
- 3-position side handle
- New dust seal design



Specifications

| | | |
|----------------------|---|--------|
| Capacity | Wheel Dia | 150mm |
| | Hole Dia | 22.2mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 1,200W | |
| No Load Speed | 8,500/min | |
| Overall Length | 391mm | |
| Weight | 2.8kg | |
| Standard Accessories | Side Handle, Depressed Center Wheel, Wrench | |

MRP: ₹ 13,220/-



G 18ST
180mm Disc Grinder
with Trigger Switch

999059 



Features

- Halved stator coils for sufficient cooling efficiency increase motor durability
- Motor is protected from dust and debris through the labyrinth construction
- Large switch lever for more control



| Specifications | | |
|----------------------|---------------------|---------|
| Capacity | Wheel Dia | 180mm |
| | Hole Dia | 22.23mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 2,000W | |
| No Load Speed | 8,500/min | |
| Overall Length | 469mm | |
| Weight | 4.9kg | |
| Standard Accessories | Side Handle, Wrench | |

MRP: ₹ 10,820/-

G 18SH2
180mm Disc Grinder
with Trigger Switch

999061 



Features

- Designed with reliability & robustness
- Increased service life of carbon brush
- Dust proof construction



| Specifications | | |
|----------------------|---------------------|---------|
| Capacity | Wheel Dia | 180mm |
| | Hole Dia | 22.23mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 2,000W | |
| No Load Speed | 8,500/min | |
| Overall Length | 463mm | |
| Weight | 4.3kg | |
| Standard Accessories | Side Handle, Wrench | |

MRP: ₹ 14,050/-

G 18BYE

999061 



Features

- Safety function - Brake function, kickback protection system, 0 voltage restart protection, overload protection & Over heat protection
- Soft start
- Tool less wheel guard
- Detachable filter



| Specifications | | |
|----------------------|---|---------|
| Capacity | Wheel Dia | 180mm |
| | Hole Dia | 22.23mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 2,200W | |
| No Load Speed | 6600/min | |
| Overall Length | 468mm | |
| Weight | 4kg | |
| Standard Accessories | Depressed center Wheel, Side Handle, Wrench | |

MRP: ₹ 26,700/-




LARGE ANGLE GRINDERS

Cordless

G 18SW2 180mm Disc Grinder with Trigger Switch

Chargers/
Batteries

999059 



Drilling

Features

- Halved stator coils for sufficient cooling efficiency increase motor durability
- Motor is protected for dust and debris through the labyrinth construction
- Soft grip handle
- Large switch lever for more control



Demolition

| Specifications | | |
|----------------------|---------------------|---------|
| Capacity | Wheel Dia | 180mm |
| | Hole Dia | 22.23mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 2,200W | |
| No Load Speed | 8,500/min | |
| Overall Length | 469mm | |
| Weight | 4.9kg | |
| Standard Accessories | Side Handle, Wrench | |

MRP: ₹ 14,500/-

Fastening

G 18SE4 180mm Disc Grinder with Trigger Switch

Grinding

999061 



Polishing &
Sanding

Features

- Small and high power split core motor provides less weight
- Vibration-absorbing side handle
- Tool-less wheel guard



Sawing

| Specifications | | |
|----------------------|---------------------|---------|
| Capacity | Wheel Dia | 180mm |
| | Hole Dia | 22.23mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 2,400W | |
| No Load Speed | 8,500/min | |
| Overall Length | 492mm | |
| Weight | 5.9kg | |
| Standard Accessories | Side Handle, Wrench | |

MRP: ₹ 16,830/-

Cutting

G 23ST 230mm Disc Grinder with Trigger Switch

Planing &
Routing

999059 



Miscellaneous

Features

- Halved stator coils for sufficient cooling efficiency increase motor durability
- Motor is protected for dust and debris through the labyrinth construction
- Large switch lever for more control



Pneumatic

| Specifications | | |
|----------------------|---------------------|---------|
| Capacity | Wheel Dia | 230mm |
| | Hole Dia | 22.23mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 2,000W | |
| No Load Speed | 6,600/min | |
| Overall Length | 469mm | |
| Weight | 5.1kg | |
| Standard Accessories | Side Handle, Wrench | |

MRP: ₹ 13,430/-

G 23SC4
230mm Disc Grinder
with Trigger Switch

999061 



Features

- Small and high power split core motor provides less weight
- Vibration-absorbing side handle
- Tool-less wheel guard



| Specifications | | |
|----------------------|---------------------|---------|
| Capacity | Wheel Dia | 230mm |
| | Hole Dia | 22.23mm |
| Spindle Thread | M14 x 2 | |
| Power Input | 2,400W | |
| No Load Speed | 6,600/min | |
| Overall Length | 492mm | |
| Weight | 6.1kg | |
| Standard Accessories | Side Handle, Wrench | |

MRP: ₹ 17,340/-

GP 2S2
25mm Hand Grinder

999088 



Features

- All ball bearing construction
- Easy-to-grip housing
- Internal carbon brush



| Specifications | | |
|----------------------|-----------------------|------|
| Capacity | Collet Chuck | 6mm |
| | Max. Wheel Dia | 25mm |
| Power Input | 520W | |
| No Load Speed | 29,000/min | |
| Overall Length | 359.4mm | |
| Weight | 1.7kg | |
| Standard Accessories | Side Handle, Wrenches | |

MRP: ₹ 14,630/-

GP 3V
25mm Electronic Hand Grinder

BRUSHLESS




Features

- Power Input 760W
- Brushless motor technology
- Variable speed by dial
- Easy to grip housing
- Electronic control soft start & constant speed



| Specifications | | |
|----------------------|-------------------------------------|------|
| Capacity | Collet Chuck | 6mm |
| | Max. Wheel Dia | 25mm |
| Power Input | 760W | |
| No Load Speed | 7,000-29,000/min | |
| Overall Length | 406mm | |
| Weight | 1.8kg | |
| Standard Accessories | Side handle, collet chuck, Wrenches | |


MRP: ₹ 19,980/-



SAWING TOOLS

Cordless

C 7SS 190mm Circular Saw

999043 



Features

- Rigid aluminium base for fine cut
- Side handle easy to grip
- Backward dust emission



| Specifications | | |
|----------------------|-----------------------|-------|
| Capacity | Blade Dia. | 190mm |
| | Max Cutting depth 90° | 68mm |
| | Max Cutting depth 45° | 46mm |
| Bevel Capacity | 0-45° | |
| Power Input | 1,050W | |
| No Load Speed | 5,500/min. | |
| Overall Length | 291mm | |
| Weight | 3.4kg | |
| Standard Accessories | Blade, Guide, Wrench | |

MRP: ₹ 7,830/-


Chargers/
Batteries

Drilling

Demolition

Fastening

C 7ST 185mm Circular Saw

999043 



Features

- Power input 1,710W
- Enhanced max cut depth
- Soft grip handle for reduced vibration & increased comfort



| Specifications | | |
|----------------------|-----------------------|--------|
| Capacity | Blade Dia. | 185mm |
| | Max Cutting depth 90° | 62mm |
| | Max Cutting depth 45° | 47.5mm |
| Bevel Capacity | 0-45° | |
| Power Input | 1,710W | |
| No Load Speed | 6,000/min | |
| Overall Length | 310mm | |
| Weight | 4.3kg | |
| Standard Accessories | Blade, Guide, Wrench | |

MRP: ₹ 12,000/-

Grinding

Polishing &
Sanding

Sawing

Cutting

C 9SA3 235mm Circular Saw

999038 



Features

- 4m cord
- Convenient cord holder
- Aluminium saw cover
- Soft grip handle
- Large knob easy to adjust cut depth



| Specifications | | |
|----------------------|--|-------|
| Capacity | Blade Dia. | 235mm |
| | Max Cutting depth 90° | 86mm |
| | Max Cutting depth 45° | 65mm |
| Power Input | 2,000W | |
| No Load Speed | 5,200/min | |
| Overall Length | 397mm | |
| Weight | 7.0kg | |
| Standard Accessories | Blade, Side Handle, Guide, Bolt, Wrench, Dust Collector, Short Lever | |

MRP: ₹ 22,000/-


Planing &
Routing

Miscellaneous

Pneumatic



C 10FCE2
255mm Compound
Miter Saw

999065 



Features

- Thumb actuated positive miter stops for quick and easy adjustment
- Soft grip handle
- Equipped with chip deflector
- Pivoting Sub-Fence for supporting larger stock



| Specifications | | |
|---------------------------|---|--------------------------|
| Capacity | Blade Dia. | 255mm |
| | (HxW) Cross Cut 0° | 59 x 144mm or 89 x 101mm |
| | (HxW) Miter Cut 45° | 59 x 102mm or 89 x 70mm |
| | (HxW) Miter Cut 52° | 59 x 89mm or 89 x 54mm |
| | (HxW) Bevel Cut 45° | 41 x 144mm |
| | Compound Miter 45° and Beve 45° | 41 x 102mm |
| Power Input | 1,520W | |
| No Load Speed | 5,000/min | |
| Miter Angle: | Right | 0 – 52° |
| | Left | 0 – 52° |
| Bevel Angle | Left | 0 – 45° |
| Positive Miter Angle Stop | 0, 15, 22.5, 31.6 and 45° | |
| Dimensions | 460 x 628 x 561mm | |
| Weight | 11.5kg | |
| Standard Accessories | Blade, Dust Bag, Vise Assy, Sub Fence, Wrenches | |

MRP: ₹ 26,100/-

C 12FDHB
305mm Compound
Miter Saw

999065 



Features

- Xact Cut LED Shadow Line System - Accurately indicates where the blade will cut on the material
- Compound Cutting - Wide range of miter and bevel cutting options
- Fences - 7" tall sliding fences to support vertically & nested cut molding
- Extra large base for great support & handling of material
- Adjustment - Up-front miter and locks to easily adjust cut angles to best suit the application
- New ergonomic D-handle design for less vibration



| Specifications | |
|--------------------------------|-----------------------------|
| Blade Dia. | 305mm |
| Arbor | 25.4 mm |
| No-Load Speed | 4,300 RPM |
| Miter Angle | 0-52° L & R |
| Bevel Angle | 0-48° L & R |
| Cut Capacity at 90° | 31.75 x 203mm or 157 x 24mm |
| Cut at 45° Miter (Left) | 32 x109mm or 80 x 20mm |
| Cut at 45° Miter (Right) | 32 x110mm or 100 x 15mm |
| Cut at 45° Bevel (Left) | 0.8 x 203mm |
| Cut at 45° Bevel (Right) | 17 x 203mm |
| Cut at 45° Miter/Bevel (Left) | 20 x109mm |
| Cut at 45° Miter/Bevel (Right) | 109 x17mm |
| Weight | 20 kg |

MRP: ₹ 41,000/-

SAWING TOOLS

FCJ 65V3 65mm Jig Saw

999041 



Features

- Variable speed dial
- Large soft grip for comfortable operation
- Motor with two ball-bearings for longer life and efficient power transmission
- Connectable directly with a dust collector without adapter



| Specifications | | |
|-----------------------|---|------|
| Capacity | Wood | 65mm |
| | Mild Steel Plate | 6mm |
| | Min. Cutting Radius | 25mm |
| Base Tilt Angle | 45° Right/Left | |
| Power Input | 400W | |
| Length of Stroke | 18mm | |
| No-Load Speed(stroke) | 0-3,000/min | |
| Overall Length | 197mm | |
| Weight | 1.5kg | |
| Standard Accessories | Blade, Splinter Guard, Chip Cover, Wrench | |

MRP: ₹ 8,550/-

CJ 90VST2 AC 90mm Jig Saw

999041 



Features

- Variable speed dial
- Larger lever for quick and easy, tool-less blade change
- 4-mode orbital action
- Soft grip handle
- Powerful dust blower keeps debris away



| Specifications | | |
|-----------------------|--|------|
| Capacity | Wood | 90mm |
| | Mild Steel Plate | 10mm |
| | Min. Cutting Radius | 25mm |
| Max Cutting Angle | 45° Right/Left | |
| Power Input | 705W | |
| Length of Stroke | 26mm | |
| No-Load Speed(stroke) | 850-3,000/min | |
| Overall Length | 215mm | |
| Weight | 2.2kg (without cord) | |
| Standard Accessories | Blade, Wrench, Carrying Case, Dust Collector | |

MRP: ₹ 11,660/-



Cordless

Chargers/
Batteries

Drilling

Demolition

Fastening

Grinding

Polishing &
Sanding

Sawing

Cutting

Planing &
Routing

Miscellaneous

Pneumatic

CR 13V2
130mm Reciprocating Saw

999043 




Features

- High cutting speed with Heavy-duty Motor
- Straight cutting action
- Quick blade change by lever
- Blade mount reversible to cut upward or downward
- Large switch to operate in upside-down
- Newly-designed front cover and handle to hold
- 150mm Curved blade included as standard



| Specifications | | |
|------------------------|--------------------------------|-------|
| Capacity | Pipe | 130mm |
| | Steel Plate | 19mm |
| | Wood | 300mm |
| Power Input | 1,010W | |
| Length of Stroke | 29mm | |
| No Load Speed (stroke) | 0-2,800/min. | |
| Overall Length | 435mm | |
| Weight | 3.3kg | |
| Standard Accessories | Blade, Wrenches, Carrying Case | |

MRP: ₹ 21,840/-

 Double Insulation

 Variable Speed



Cordless

Chargers/
Batteries

Drilling

Demolition

Fastening

Grinding

Polishing &
Sanding

Sawing

Cutting


Planing &
Routing

Miscellaneous

Pneumatic

CHAIN SAW / CUTTERS

CS 40Y 400mm Chain Saw

999038 



Features


- Balanced design for more control
- Tool-less chain adjuster
- Large switch lever with soft start and over-load protection
- Chain oil flow adjuster
- Front and rear handles with soft grip



| Specifications | |
|----------------------|--|
| Voltage | 230V |
| Power Input | 2,000W |
| No Load Chain Speed | 14.5m/s |
| Chain Pitch | 3/8" |
| Chain Gauge | 0.05" |
| Guide Bar Length | 400mm |
| Type of Guide Bar | Sprocket Nose |
| Oil Tank Capacity | 150mL |
| Dimensions (LxWxH) | 490x217x220mm |
| Dry Weight | 5.5kg |
| Standard Accessories | Guide Bar, Saw Chain, Plug Clip Chain Case |

MRP: ₹ 19,800/-

CM 4ST 110mm Cutter

999043 



Features


- Dust Proof Switch
- Power input 1,300W with overload durability



| Specifications | | |
|----------------------|---------------|-------|
| Capacity | Wheel Dia. | 110mm |
| | Max Cut Depth | 34mm |
| Power Input | 1,300W | |
| No Load Speed | 13,000/min | |
| Overall Length | 214mm | |
| Weight | 2.9kg | |
| Standard Accessories | Wrench | |

MRP: ₹ 6,580/-

CM 4SB2 110mm Cutter

999043 



Features


- Metal bush on a ball-bearing and sealed armature coil for durability
- Soft grip handle
- Tool-less depth adjustment



| Specifications | | |
|----------------------|--|-------|
| Capacity | Wheel Dia. | 110mm |
| | Max Cut Depth | 34mm |
| | Cut Depth per cut | 20mm |
| Power Input | 1,320W | |
| No Load Speed | 11,500/min | |
| Overall Length | 204mm | |
| Weight | 2.8kg | |
| Standard Accessories | Water Plug, Rubber Connector, Wrenches, Vinyl Hose | |

MRP: ₹ 6,750/-

CC 14STA
355mm High-Speed
Cut-off Machine

370779 

Features


- Lightweight design
- Quick lock vise
- Spark diversion guard
- With Spindle lock mechanism



| Specifications | |
|-------------------------------|-----------------------|
| Capacity : Cut-off Wheel Dia. | 355mm |
| Power Input | 2,000W |
| No Load Speed | 3,900/min. |
| Dimensions (L x W x H) | 584 x 287 x 610mm |
| Weight | 14.1kg |
| Standard Accessories | Cut-off Wheel, Wrench |

MRP: ₹ 13,740/-

CC 14STD
355mm High-Speed
Cut-off Machine

370779 

Features


- With powerful motor of 2,200W
- With Spindle lock mechanism
- D-shaped handle
- Quick lock vise
- Spark diversion guard



| Specifications | |
|-------------------------------|-----------------------|
| Capacity : Cut-off Wheel Dia. | 355mm |
| Power Input | 2,200W |
| No Load Speed | 3,800/min |
| Max Working Perphera Speed | 4,800m/min. |
| Dimensions (L x W x H) | 590 x 300 x 640mm |
| Weight | 17.0kg |
| Standard Accessories | Cut-off Wheel, Wrench |

MRP: ₹ 17,970/-

CC 14STDU
355mm High-Speed
Cut-off Machine

370779 

Features

- With powerful motor & Soft start
- With Spindle lock mechanism
- D-shaped handle
- Quick lock vise
- Spark diversion guard



| Specifications | |
|------------------------------|-----------------------|
| Capacity: Cut-off Wheel Dia. | 355mm |
| Power Input | 2,200W |
| No Load Speed | 3,800/min |
| Max Working Perphera Speed | 4,800m/min. |
| Dimensions (L x W x H) | 590 x 300 x 650mm |
| Weight | 17.0kg |
| Standard Accessories | Cut-off Wheel, Wrench |

MRP: ₹ 21,740/-

P 20ST
82mm Planer

999021 

Features

- Max cutting depth of 1.5mm
- Compact & light weight
- Rabbeting depth: 9mm
- Easy to adjust cutting depth by knob
- Optional dust bag or elbow can be connected



| Specifications | |
|-------------------------|--|
| Capacity: Cutting Width | 82mm |
| Max Cutting Depth | 1.5mm |
| Power Input | 580W |
| No Load Speed | 17,000/min |
| Overall Length | 296mm |
| Weight | 2.5kg |
| Standard Accessories | Blades, Blade Setting Gauge, Guide, Wrench |

MRP: ₹ 8,030/-



Double Insulation



Spindle Lock



Electronic Soft Start Control